



## SMART LOTIS 3.2 LED DE

Smart lotis is the best known fixture within the Smart family. The deeply recessed cone which holds the light source inspired the designers to create a very versatile spot to be combined with multiple accessories. This family's styling is based on our most popular designs. Concretely this means that the luminaires consist of a LED module which can be combined with one of three trims to suit your needs. The new spotlights can be combined with Smart mask, Smart surface box or Smart surface tubed to form the perfect solution for any interior. Choose a white, black or gold finishing.

Art. Nr. US\_12446709

### SPECIFICATIONS

Lamp	1x LED Array	
Driver	driver excluded - requires housing or Smart surface box with driver (see below)	
Cut-out size	ø 2"3/4	
Weight	0.79kg	
Min. distance	4 in.	
Location rating	suitable for damp locations	
Glow wire test		
webterm_lifetime	L80 B20 @ 50.000hrs	
CRI	90	
Power supply	350mA	500mA
	17.8Vf	18.4Vf
webterm_connected_load	6.2W	9.2W
webterm_lumen	601lm	809lm
Efficacy	97lm/W	88lm/W
UGR	21	22
Adjustability	Not Applicable	
Remark	! has to be used with Smart surface box, Smart surface tubed or appropriate housing ! can be combined with Smart mask	

	WARM WHITE 2700K / CRI 90+					WARM WHITE 3000K / CRI 90+					! CCEA Chicago Micro LED & Airtight per ASTM-E283-04 (when used with IC-UAT) 3500K / CRI 90+				
	MEDIUM 25°	FLOOD 40°	SPOT 15°	FROSTED GLASS 25°	MICRO PRISMATIC GLASS 25°	MEDIUM 25°	FLOOD 40°	SPOT 15°	FROSTED GLASS 25°	MICRO PRISMATIC GLASS 25°	FROSTED GLASS 25°	FLOOD 40°	MEDIUM 25°	SPOT 15°	MICRO PRISMATIC GLASS 25°
black struc	US_12441032	US_12441232	US_12441632	US_12443732	US_12446732	US_12441432	US_12441532	US_12441732	US_12443432	US_12446432	US_12443132	US_12445032	US_12445132	US_12445232	US_12446132
gold	US_12441046	US_12441246	US_12441646	US_12443746	US_12446746	US_12441446	US_12441546	US_12441746	US_12443446	US_12446446	US_12443146	US_12445046	US_12445146	US_12445246	US_12446146
white struc	US_12441009	US_12441209	US_12441609	US_12443709	<b>US_12446709</b>	US_12441409	US_12441509	US_12441709	US_12443409	US_12446409	US_12443109	US_12445009	US_12445109	US_12445209	US_12446109