



QBINI ROUND IN LED DE

A portmanteau of 'cubic' and 'mini', Qbini introduces modular, miniature, recessed LED lighting solutions to residential and hospitality venues and boutiques. Qbini allows to effortlessly express a unique lighting concept in every project. Available in a load of shapes, frames, colours and accessories, Qbini combines choice with exclusive design and high-quality lighting technology. Qbini is offered with clear, frosted or microprismatic lenses and can be combined with 2 different frames: with or without a trim. Both of them are available in 1x, 2x, 3x or 4x lamp configurations. Mix and match and create your preferred configuration.

Art. Nr. **US_14102209**

SPECIFICATIONS

| | | |
|------------------------|---|--------|
| Lamp | 1x LED Array | |
| Driver | driver excluded - requires housing | |
| Weight | 0.6kg | |
| Min. distance | 0.3 ft | |
| Location rating | suitable for damp locations | |
| Glow wire test | | |
| webterm_lifetime | L80 B20 @ 50.000hrs | |
| CRI | 90 | |
| Power supply | 350mA | 500mA |
| | 8.5Vf | 8.8Vf |
| webterm_connected_load | 3W | 4.3W |
| webterm_lumen | 313lm | 417lm |
| Efficacy | 104lm/W | 97lm/W |
| UGR | 20 | 21 |
| Adjustability | Not Applicable | |
| Remark | ! must be used with Qbini (trimless) frame and appropriate housing ! CCEA Chicago Plenum rated & Airtight per ASTM-E283-04 (when used with IC-UAT box) | |

| | WARM WHITE 2700K / CRI 90+ | | | | | WARM WHITE 3000K / CRI 90+ | | | | | NEUTRAL WHITE 3500K / CRI 90+ | | | WARM WHITE 3500K / CRI 90+ | | |
|----------------|-------------------------------|---------------|--------------------------------------|---|--|-------------------------------|--------------------|--------------------------------------|---|--|----------------------------------|---------------|--------------------------------------|---|--|--|
| | FLOOD 40° | MEDIUM 25° | FROSTED LENS WIDE FLOOD 60° | MICRO PRISMATIC LENS FLOOD 40° | MICRO PRISMATIC LENS MEDIUM 25° | FLOOD 40° | MEDIUM 25° | FROSTED LENS WIDE FLOOD 60° | MICRO PRISMATIC LENS FLOOD 40° | MICRO PRISMATIC LENS MEDIUM 25° | FLOOD 40° | MEDIUM 25° | FROSTED LENS WIDE FLOOD 60° | MICRO PRISMATIC LENS FLOOD 40° | MICRO PRISMATIC LENS MEDIUM 25° | |
| black struc | US_14101132 | US_14101232 | US_14101332 | US_14101432 | US_14101532 | US_14102132 | US_14102232 | US_14102332 | US_14102432 | US_14102532 | US_14105132 | US_14105232 | US_14105332 | US_14105432 | US_14105532 | |
| gold | US_14101146 | US_14101246 | US_14101346 | US_14101446 | US_14101546 | US_14102146 | US_14102246 | US_14102346 | US_14102446 | US_14102546 | US_14105146 | US_14105246 | US_14105346 | US_14105446 | US_14105546 | |
| white struc | US_14101109 | US_14101209 | US_14101309 | US_14101409 | US_14101509 | US_14102109 | US_14102209 | US_14102309 | US_14102409 | US_14102509 | US_14105109 | US_14105209 | US_14105309 | US_14105409 | US_14105509 | |