



QBINI ROUND OUT LED DE

A portmanteau of 'cubic' and 'mini', Qbini introduces modular, miniature, recessed LED lighting solutions to residential and hospitality venues and boutiques. Qbini allows to effortlessly express a unique lighting concept in every project. Available in a load of shapes, frames, colours and accessories, Qbini combines choice with exclusive design and high-quality lighting technology. Qbini is offered with clear, frosted or microprismatic lenses and can be combined with 2 different frames: with or without a trim. Both of them are available in 1x, 2x, 3x or 4x lamp configurations. Mix and match and create your preferred configuration.

Art. Nr. **US_14111232**

SPECIFICATIONS

| | | |
|------------------------|---|--------|
| Lamp | 1x LED Array | |
| Driver | driver excluded - requires housing | |
| Weight | 0.6kg | |
| Min. distance | 0.3 ft | |
| Location rating | suitable for damp locations | |
| Glow wire test | | |
| webterm_lifetime | L80 B20 @ 50.000hrs | |
| CRI | 90 | |
| Power supply | 350mA | 500mA |
| | 8.5Vf | 8.8Vf |
| webterm_connected_load | 3W | 4.3W |
| webterm_lumen | 229lm | 305lm |
| Efficacy | 76lm/W | 71lm/W |
| UGR | 4 | 5 |
| Adjustability | Not Applicable | |
| Remark | ! must be used with Qbini (trimless) frame and appropriate housing ! CCEA Chicago Plenum rated & Airtight per ASTM-E283-04 (when used with IC-UAT box) | |

| | WARM WHITE 2700K / CRI 90+ | | | | | WARM WHITE 3000K / CRI 90+ | | | | | NEUTRAL WHITE 3500K / CRI 90+ | | | WARM WHITE 3500K / CRI 90+ | | |
|----------------|-------------------------------|--------------------|--------------------------------------|---|--|-------------------------------|---------------|--------------------------------------|---|--|----------------------------------|---------------|--------------------------------------|---|--|--|
| | FLOOD 40° | MEDIUM 25° | FROSTED LENS WIDE FLOOD 55° | MICRO PRISMATIC LENS FLOOD 40° | MICRO PRISMATIC LENS MEDIUM 25° | FLOOD 40° | MEDIUM 25° | FROSTED LENS WIDE FLOOD 55° | MICRO PRISMATIC LENS FLOOD 40° | MICRO PRISMATIC LENS MEDIUM 25° | FLOOD 40° | MEDIUM 25° | FROSTED LENS WIDE FLOOD 55° | MICRO PRISMATIC LENS FLOOD 40° | MICRO PRISMATIC LENS MEDIUM 25° | |
| black struc | US_14111132 | US_14111232 | US_14111332 | US_14111432 | US_14111532 | US_14112132 | US_14112232 | US_14112332 | US_14112432 | US_14112532 | US_14115132 | US_14115232 | US_14115332 | US_14115432 | US_14115532 | |
| gold | US_14111146 | US_14111246 | US_14111346 | US_14111446 | US_14111546 | US_14112146 | US_14112246 | US_14112346 | US_14112446 | US_14112546 | US_14115146 | US_14115246 | US_14115346 | US_14115446 | US_14115546 | |
| white struc | US_14111109 | US_14111209 | US_14111309 | US_14111409 | US_14111509 | US_14112109 | US_14112209 | US_14112309 | US_14112409 | US_14112509 | US_14115109 | US_14115209 | US_14115309 | US_14115409 | US_14115509 | |