



## SMART LOTIS 3.2 WET LED DE

Smart lotis is the best known fixture within the Smart family. The deeply recessed cone which holds the light source inspired the designers to create a very versatile spot to be combined with multiple accessories. This family's styling is based on our most popular designs. Concretely this means that the luminaires consist of a LED module which can be combined with one of three trims to suit your needs. The new spotlights can be combined with Smart mask, Smart surface box or Smart surface tubed to form the perfect solution for any interior. Choose a white, black or gold finishing.

Art. Nr. US\_12445309

### SPECIFICATIONS

Driver	driver excluded - requires housing	
Cut-out size	Ø 2"3/4	
Weight	0.6kg	
Min. distance	4 in.	
Location rating	suitable for wet locations	
Glow wire test		
webterm_lifetime	L80 B20 @ 50.000hrs	
CRI	90	
Power supply	350mA	<b>500mA</b>
	17.8Vf	<b>18.4Vf</b>
webterm_connected_load	6.2W	<b>9.2W</b>
webterm_lumen	594lm	<b>799lm</b>
Efficacy	96lm/W	<b>87lm/W</b>
UGR	20	<b>21</b>
Adjustability	Not Applicable	
Remark	! has to be used with appropriate housing ! IC housing is suitable for damp and wet locations, depending on the fixture selection ! can be combined with Smart mask	

	NEUTRAL WHITE 3500K / CRI 90+					WARM WHITE 3000K / CRI 90+					WARM WHITE 2700K / CRI 90+				
	FROSTED GLASS 25°	MICRO PRISMATIC GLASS 25°	FLOOD 40°	MEDIUM 25°	SPOT 15°	FROSTED GLASS 25°	MICRO PRISMATIC GLASS 25°	FLOOD 40°	MEDIUM 25°	SPOT 15°	FROSTED GLASS 25°	MICRO PRISMATIC GLASS 25°	FLOOD 40°	MEDIUM 25°	SPOT 15°
black struc	US_12440132	US_12442132	US_12444332	US_12444432	US_12444532	US_12440432	US_12442432	US_12444632	US_12444732	US_12444832	US_12440732	US_12442732	US_12444932	US_12445332	US_12445432
gold	US_12440146	US_12442146	US_12444346	US_12444446	US_12444546	US_12440446	US_12442446	US_12444646	US_12444746	US_12444846	US_12440746	US_12442746	US_12444946	US_12445346	US_12445446
white struc	US_12440109	US_12442109	US_12444309	US_12444409	US_12444509	US_12440409	US_12442409	US_12444609	US_12444709	US_12444809	US_12440709	US_12442709	US_12444909	<b>US_12445309</b>	US_12445409